



Flooding suspended powerful lighting, superior optical design for Commercial Projects!

HIGH BAY LED



POWER without high energy costs!



Wide Loyal's High-Bay Lighting luminaires are designed for applications of 20 feet (6 meters) or more. A wide range of lighting fixtures provide specific light patterns for your high bay lighting applications, including maintenance lighting, warehouse lighting, recreation center lighting, hangar lighting and storage lighting. Wide Loyal Lighting indoor lighting fixtures provide industrial and commercial lighting to help improve safety and energy efficiency while enhancing productivity.

The high system efficiency and long service life makes it a genuine alternative and a 1:1 replacement for conventional systems equipped with HIE/HIT or HSE/HST lamps. In comparison, the Compact High Bay LED saves up to 68 % energy, and minimal maintenance costs for regular relamping.






See reverse side for specifications.

Wide Loyal Developments Ltd. • Los Angeles, CA • Seattle, WA • Vancouver, BC

US & Canada: 1-888-303-0931 (Toll Free) Fax: 1-888-303-0932 www.wideloyal.com e-mail: sales@wideloyal.com

We also provide customers with comprehensive technical advice and installation guidelines to ensure that **High Bays** are installed properly.



TECHNICAL SPECIFICATIONS									
Item Number	LH-WL-C150W	LH-WL-M150W	LH-WL-C200W	LH-WL-M200W	LH-WL-C300W	LH-WL-M300W	LH-WL-C400W	LH-WL-M400W	LH-WL-M500W
Descriptions	LED High Bay		LED High Bay		LED High Bay		LED High Bay		LED High Bay
Picture									
Voltage	AC 110-240V		AC 110-240V		AC 110-240V		AC 110-240V		AC 110-240V
Working Temperature	-45° ~ 65°C		-45° ~ 65°C		-45° ~ 65°C		-45° ~ 65°C		-45° ~ 65°C
Working Humidity	≤95%		≤95%		≤95%		≤95%		≤95%
Wattage	150W		200W		300W		400W		500W
Power Supply									
PF	>90%		>90%		>90%		>90%		>95%
LED	CREE XBD*90		CREE XBD*130		CREE XBD*192		CREE XBD*280		CREE XBD*350
Luminous Flux	13800 Lm		18400 Lm		27600 Lm		36800 Lm		46000 Lm
CCT	3000/4000/6000K		3000/4000/6000K		3000/4000/6000K		3000/4000/6000K		3000/4000/6000K
CRI	>80Ra		>80Ra		>80Ra		>80Ra		>80Ra
Beam Angle	60°		60°		60°		60°		60°
IP Code	IP65		IP65		IP65		IP65		IP65
Certificate	UL CE RoHS		UL CE RoHS		UL CE RoHS		UL CE RoHS		UL CE RoHS
Lifespan	35,000 Hours		35,000 Hours		35,000 Hours		35,000 Hours		35,000 Hours
Size									
Material	Aluminum		Aluminum		Aluminum		Aluminum		Aluminum
Gross Weight	9.5Kg		12Kg		14 Kg		15 Kg		15 Kg
Package Dimension									
Storage Condition	-40°C ~ 80°C		-40°C ~ 80°C		-40°C ~ 80°C		-40°C ~ 80°C		-40°C ~ 80°C
Warranty	1 Year		1 Year		1 Year		1 Year		1 Year

