



- Water-proof
- Super Bright
- Dimmable

Highly Efficient, Excellent Performance and Durability for Roadways and Freeways!

STREET-LIGHT



Pure Performance!



Wide Loyal Street-Light LEDs has been designed from the bottom up as a totally optimized LED street luminaire that delivers incredible efficiency, without sacrificing application performance, Wide Loyal street lighting solutions are available to enhance quality of life and improve infrastructure in an efficient and cost-effective manner.

The Wide Loyal Street-Light LED is an ideal replacement for outdated high-pressure sodium fixtures and can provide increased value while displacing a range of incumbent technologies from 70W up to 400W. These luminaires are ideal for any street/roadway applications.

See reverse side for specifications.

Wide Loyal Developments Ltd. • Los Angeles, CA • Seattle, WA • Vancouver, BC

US & Canada: 1-888-303-0931 (Toll Free) Fax: 1-888-303-0932 www.wideloyal.com e-mail: sales@wideloyal.com

Wide Loyal Street LED fixtures enhance illumination along city streets while providing savings through increased energy efficiency, decreased maintenance needs and longer-rated lifetimes.



TECHNICAL SPECIFICATIONS			
Item Number	Picture	Details	
LH-CK31A	   	Specifications	
		Voltage	AC 100-240V/277V 50/60Hz
		Wattage	35W
		LED Chip	Philips Luxeon Rebel ES 
		Power Supply	Mean Well
		Luminous Flux	3325Lm +/- 5%
		IP Rating	IP66
		CCT	2700-6500K
		CRI	>75
		PF	>0.92
		THD	<15%
		Finish	Silver, Black
		Dimensions	
		Fixture Info	431*316*136mm, 5.3Kg
		Aperture Diameter	Φ60 mm
Packing Info	480*370*200mm, 6.3Kg		
Remarks			
Certifications	UL ETL RoHS DLC FCC		
Standards	LM-79 LM-80		
Warranty	2 Years		
LH-CK32A	   	Specifications	
		Voltage	AC 100-240V/277V 50/60Hz
		Wattage	65W
		LED Chip	Philips Luxeon Rebel ES 
		Power Supply	Mean Well
		Luminous Flux	6175Lm +/- 5%
		IP Rating	IP66
		CCT	2700-6500K
		CRI	>75
		PF	>0.92
		THD	<15%
		Finish	Silver, Black
		Dimensions	
		Fixture Info	504*316*136mm, 6.1Kg
		Aperture Diameter	Φ60 mm
Packing Info	555*370*200mm, 7.3Kg		
Remarks			
Certifications	UL ETL RoHS DLC FCC		
Standards	LM-79 LM-80		
Warranty	2 Years		



Wide Loyal Developments Ltd. • Los Angeles, CA • Seattle, WA • Vancouver, BC

US & Canada: 1-888-303-0931 (Toll Free) Fax: 1-888-303-0932 www.wideloyal.com e-mail: sales@wideloyal.com

TECHNICAL SPECIFICATIONS			
Item Number	Picture	Details	
LH-CK33A	   	Specifications	
		Voltage	AC 100-240V/277V 50/60Hz
		Wattage	100W
		LED Chip	Philips Luxeon Rebel ES 
		Power Supply	Mean Well
		Luminous Flux	9500Lm +/- 5%
		IP Rating	IP66
		CCT	2700-6500K
		CRI	>75
		PF	>0.92
		THD	<15%
		Finish	Silver, Black
		Dimensions	
		Fixture Info	577*316*136mm, 7.3Kg
		Aperture Diameter	Φ60 mm
Packing Info	630*370*200mm, 8.6Kg		
Remarks			
Certifications	UL ETL RoHS DLC FCC		
Standards	LM-79 LM-80		
Warranty	2 Years		
LH-CK34A	   	Specifications	
		Voltage	AC 100-240V/277V 50/60Hz
		Wattage	135W
		LED Chip	Philips Luxeon Rebel ES 
		Power Supply	Mean Well
		Luminous Flux	12825Lm +/- 5%
		IP Rating	IP66
		CCT	2700-6500K
		CRI	>75
		PF	>0.92
		THD	<15%
		Finish	Silver, Black
		Dimensions	
		Fixture Info	650*316*136mm, 8.2Kg
		Aperture Diameter	Φ60 mm
Packing Info	705*370*200mm, 9.6Kg		
Remarks			
Certifications	UL ETL RoHS DLC FCC		
Standards	LM-79 LM-80		
Warranty	2 Years		
LH-CK35A	   	Specifications	
		Voltage	AC 100-240V/277V 50/60Hz
		Wattage	165W
		LED Chip	Philips Luxeon Rebel ES 
		Power Supply	Mean Well
		Luminous Flux	15675Lm +/- 5%
		IP Rating	IP66
		CCT	2700-6500K
		CRI	>75
		PF	>0.92
		THD	<15%
		Finish	Silver, Black
		Dimensions	
		Fixture Info	723*316*136mm, 9.0Kg
		Aperture Diameter	Φ60 mm
Packing Info	780*370*200mm, 10.6Kg		
Remarks			
Certifications	UL ETL RoHS DLC FCC		
Standards	LM-79 LM-80		
Warranty	2 Years		



Wide Loyal Developments Ltd. • Los Angeles, CA • Seattle, WA • Vancouver, BC

US & Canada: 1-888-303-0931 (Toll Free) Fax: 1-888-303-0932 www.wideloyal.com e-mail: sales@wideloyal.com

TECHNICAL SPECIFICATIONS			
Item Number	Picture	Details	
LH-CK36A	   	Specifications	
		Voltage	AC 100-240V/277V 50/60Hz
		Wattage	200W
		LED Chip	Philips Luxeon Rebel ES 
		Power Supply	Mean Well
		Luminous Flux	19000Lm +/- 5%
		IP Rating	IP66
		CCT	2700-6500K
		CRI	>75
		PF	>0.92
		THD	<15%
		Finish	Silver, Black
		Dimensions	
		Fixture Info	796*316*136mm, 9.9Kg
		Aperture Diameter	Φ60 mm
Packing Info	855*370*200mm, 11.6Kg		
Remarks			
Certifications	UL ETL RoHS DLC FCC		
Standards	LM-79 LM-80		
Warranty	2 Years		
LH-CK37A	   	Specifications	
		Voltage	AC 100-240V/277V 50/60Hz
		Wattage	230W
		LED Chip	Philips Luxeon Rebel ES 
		Power Supply	Mean Well
		Luminous Flux	21850Lm +/- 5%
		IP Rating	IP66
		CCT	2700-6500K
		CRI	>75
		PF	>0.92
		THD	<15%
		Finish	Silver, Black
		Dimensions	
		Fixture Info	869*316*136mm, 10.8Kg
		Aperture Diameter	Φ60 mm
Packing Info	930*370*200mm, 12.6Kg		
Remarks			
Certifications	UL ETL RoHS DLC FCC		
Standards	LM-79 LM-80		
Warranty	2 Years		

